



YOKOHAMA RELIABILITY. **BOTTOM LINE PERFORMANCE.**

Four tough new earthmoving tires built for your job site. Extraordinary value, proven design.



Y580H™

The directionally opposed lugs of the Y580H™ produce a self-cleaning action and provide excellent traction and flotation on muddy ground.

G-2 & L-2 APPLICATIONS



Y581H™

The Y581H™ is specially designed for operation on snow covered roads. Its directional tread pattern provides excellent traction and pulling performance.

G-2 & L-2 APPLICATIONS



Y582H™

The wide ground contact area of the Y582H™ extends overall service life and its tough tread resists heat buildup for greater reliability over long distances. Perfect for dozers moving dirt or coal in harsh environments.

G-3 & L-3 APPLICATIONS



Y583H™

The Y583H™ is optimized for outstanding durability, cut resistance as well as a long service life. Its flush tread pattern provides a large contact area and improved stability.

L-3 APPLICATIONS

Y580H™ G-2 & L-2

Size	Part #	Ply	TRA Code	Compound	Tire Type	Tread Depth (1/32")	Inflated Dimensions		Static Loaded		Ship Weight (lb.)	Max Load (lb.)	Rated Pressure (psi)	Rim Size
							Overall Diameter (in.)	Overall Width (in.)	Radius (in.)	Width (in.)				
13.00-24	130185100	10	G-2	REG	TL	34	50.4	13.6	23.3	14.6	158	5200	33	8.00TG
13.00-24	130185101	10	G-2	REG	TT	34	50.4	13.6	23.3	14.6	148	5200	33	8.00TG
13.00-24	130185102	12	G-2	REG	TL	34	50.4	13.6	23.3	14.6	172	6000	44	8.00TG
13.00-24	130185103	12	G-2	REG	TT	34	50.4	13.6	23.3	14.6	163	6000	44	8.00TG
14.00-24	130185109	10	G-2	CP	TL	36	52.8	14.8	23.8	16.1	185	6150	33	10.00VA
14.00-24	130185110	10	G-2	CP	TT	36	52.8	14.8	23.8	16.1	180	6150	33	10.00VA
14.00-24	130185111	12	G-2	CP	TL	36	52.8	14.8	23.8	16.1	201	6800	36	10.00VA
			L-2	CP	TL	36	52.8	14.8	23.4	16.5	201	13900	62	10.00VA
14.00-24	130185112	12	G-2	CP	TT	36	52.8	14.8	23.8	16.1	195	6800	36	10.00VA
			L-2	CP	TT	36	52.8	14.8	23.4	16.5	195	13900	62	10.00VA
16.9-24	130185116	10	L-2	CP	TL	36	50.9	17.7	22.9	18.9	196	7620	35	W15L
16.9-24	130185119	12	L-2	CP	TL	36	50.9	17.7	22.9	18.9	210	8330	41	W15L
17.5/65-20	130185121	10	L-2	REG	TL	31	43.2	17.4	19.4	18.1	148	7040	35	W14L
17.5-25	130185123	12	G-2	CP	TL	34	53.1	17.7	24.3	18.8	239	6400	29	14.00-1.5
			L-2	CP	TL	34	53.1	17.7	23.4	19.2	239	13600	51	14.00-1.5
18.4-24	130185129	10	L-2	REG	TL	39	54.0	18.8	23.8	19.9	231	8690	32	W16L

Y581H™ G-2 & L-2

Size	Part #	Ply	TRA Code	Compound	Tire Type	Tread Depth (1/32")	Inflated Dimensions		Static Loaded		Ship Weight (lb.)	Max Load (lb.)	Rated Pressure (psi)	Rim Size
							Overall Diameter (in.)	Overall Width (in.)	Radius (in.)	Width (in.)				
14.00-24	130185105	12	G-2	CP	TT	35	52.8	14.7	23.9	16.0	208	6800	36	10.00VA
14.00-24	130185106	14	G-2	CP	TT	35	52.8	14.7	23.9	16.0	208	7600	44	10.00VA
14.00-24	130185107	16	G-2	CP	TT	35	52.8	14.7	24.6	15.7	215	8050	51	10.00VA
14.00-24	130185108	20	G-2	CP	TT	35	52.8	14.7	24.6	15.7	244	9350	65	10.00VA
16.9-24	130185117	10	L-2	CP	TL	43	51.2	17.6	23.5	18.7	213	7620	35	W15L
16.9-24	130185120	12	L-2	CP	TL	43	51.2	17.6	23.5	18.7	227	8330	41	W15L
17.5/65-20	130185122	10	L-2	REG	TL	31	43.3	17.4	19.7	18.0	177	7040	35	W14L
17.5-25	130185124	12	L-2	CP	TL	42	53.9	17.6	24.0	19.0	268	13600	51	14.00-1.5

Y582H™ G-3 & L-3

Size	Part #	Ply	TRA Code	Compound	Tire Type	Tread Depth (1/32")	Inflated Dimensions		Static Loaded		Ship Weight (lb.)	Max Load (lb.)	Rated Pressure (psi)	Rim Size
							Overall Diameter (in.)	Overall Width (in.)	Radius (in.)	Width (in.)				
14.00-24	130185113	12	G-3	REG	TL	35	53.0	14.4	24.5	16.0	242	6800	36	10.00VA
			L-3	REG	TL	35	53.0	14.4	23.7	16.6	242	13900	62	10.00VA
14.00-24	130185114	16	G-3	REG	TL	35	53.0	14.8	24.8	15.9	261	8050	51	10.00VA
			L-3	REG	TL	35	53.0	14.8	24.0	16.4	261	16500	83	10.00VA
14.00-24	130185115	16	G-3	REG	TT	35	53.0	14.8	24.9	15.8	251	8050	51	10.00VA
			L-3	REG	TT	35	53.0	14.8	24.1	16.3	251	16500	83	10.00VA
16.9-24	130185118	10	L-3	REG	TL	36	51.0	17.4	23.3	18.5	232	7620	35	W15L
17.5-25	130185125	12	L-3	REG	TL	38	53.4	17.4	24.0	18.9	265	13600	51	14.00-1.5
17.5-25	130185127	16	L-3	REG	TL	38	53.4	17.4	24.0	18.9	278	16100	69	14.00-1.5
20.5-25	130185132	16	L-3	REG	TL	42	59.0	20.3	26.2	22.1	370	18200	51	17.00-2.0
23.5-25	130185134	16	L-3	REG	TL	53	63.2	23.5	25.8	25.8	556	20900	44	19.5-2.5

Y583H™ L-3

Size	Part #	Ply	TRA Code	Compound	Tire Type	Tread Depth (1/32")	Inflated Dimensions		Static Loaded		Ship Weight (lb.)	Max Load (lb.)	Rated Pressure (psi)	Rim Size
							Overall Diameter (in.)	Overall Width (in.)	Radius (in.)	Width (in.)				
17.5-25	130185126	12	L-3	REG	TL	38	52.8	17.1	23.5	18.9	260	13600	51	14.00-1.5
17.5-25	130185128	16	L-3	REG	TL	38	52.8	17.1	23.5	18.9	273	16100	69	14.00-1.5
20.5-25	130185131	12	L-3	REG	TL	41	58.9	20.9	26.2	22.8	360	14800	36	17.00-2.0
20.5-25	130185133	16	L-3	REG	TL	41	58.9	20.9	26.2	22.8	377	18200	51	17.00-2.0